



# Aurora C80 Handheld Computer

CILICO Aurora C80 handheld computer is with trendy, powerful, original, and professional design. It includes standard version, medical version and UHF versions, which can be extended up to 13 different versions. It not only has one 4600mAh removable battery, but also supports hot swap battery and pistol battery meanwhile, which allows 24 hours uninterrupted work. CILICO insists on original design of high integration and small size, such as built-in UHF module, PSAM etc. With elegant design and powerful performance, C80 handheld computer can be widely used in industries such as medical and health, logistics and warehouse, retail, smart manufacture, and asset management etc.

### Innovative technology smooth and more efficient operation

- C80 is equipped with Octa core 2.0GHz CPU and Android11 OS with GMS certified, which is smooth, more secure and super experience
- With 4GB RAM+64GB ROM large memory, it works smoother multitasking
- Highly integrated scanning, UHF RFID, NFC, PSAM in such small impact size
- A variety of scanning engine options to deal with all kinds of impossibilities

### Innovative batteries 24 hours full day working freely

- 4600mAh large-capacity battery which can last for more than 12 hours
- Removable battery, supporting hot swap battery and 24hours never power off

### Comprehensive management software Customized ultimate experience

- CILICO self-owned iVYAi management system, successful to achieve all the global devices management
- Independently customized IoT OS development service kit to offer u the super user experience



### Rebuilt classic 360° super protection strong and durable

- IP68, 2.5 m drop resistant, special designed for harsh environments
- It is easy to deal with during bad weather such as rain, snow and fog

### Light and large vision with easy and free hand control

- 5.72 inch full-view HD touch screen for smooth vision and easy reading
- It can be used smoothly in wet hands, gloves and complex environments
- Light device body can be operated by one hand comfortable and convenient

### Intimate design super user-experience

- Only One - click, easily access to required applications
- Double MIC design, call quality better
- Innovative industry product, highly-integrated temperature measurement and pupil lamp, more focused and professional


### Application Scenarios



Medical and healthcare



Retail



Logistics and warehouse



Smart manufacture



Railway and transportation

# C80 Specifications

## Basic Parameters

Size	162×76.8 ×13.9mm
Weight	252g(including battery)
Display	5.72inch 18:9 HD+(1440*720)
Touch panel	Gorillaglass, plated with anti-fingerprint film, supports wet hand operation
Backlit	LED Backlit
POWER	4600mAh , 3.8V removable lithium battery; spare battery(optional):150mAh More than 8hours working time , and standby time 300hours
SIM	SIM+TF: nano sim+nano sim/TF Card
USB port	Type-c, Support OTG
Network connections	4G/3G/2G, Wi-Fi, GPRS
Notification	Cue Tone; multi-color led; Vibration
Keyboard	3 virtual buttons: Back, Home, Menu
Audio frequency	A microphone, speaker, receiver

## Performance Parameter

CPU	Octa-core 2.0GHz
OS	Android 11 with GMS
Memory	Standard 4GB+64GB (LPDDR4X+EMMC), Option 3GB+32GB/6G+128G

## Working environment

Operating temperature	-10°C to 50°C
Humidity	5% to 95% (Non-condensation)
Drop specification	Within the working temperature range, it can withstand repeated falls from a height of 2.5 meters to the concrete floor
Roll Specification	Can Withstand 200 times 1.6 ft/0.5 m rolling impact; meets or exceeds IEC
Vibration	Random(10 Hz-30KHz);60 minutes per shaft
Electrostatic protection	+/- 10kv air discharge +/-6kv contact discharge
Protection level	IP68

## Wireless Communication

WWAN	Asia + Europe band: GSM:Band 2/3/5/8 WCDMA:Band 1/2/5/8 TD-SCDMA:Band 34/39 CDMA:Band BC0 TDD-LTE:Band 34/38/39/40/41 FDD-LTE:Band 1/3/5/7/8/20
------	---

American band:  
GSM:Band 2/3/5/8  
WCDMA:Band 1/2/4/5 CDMA:Band BC0  
TDD-LTE:Band 40/41  
FDD-LTE:Band B1/2/4/5/7/28A/28B

WIFI	Wifi Frequency: 2.4GHz & 5GHz Protocol: 802.11 a/b/g/n/ac/r/e/i Fast Roaming
navigation	Beidou, Glonass, GPS, Galileo, QZSS
Version	Bluetooth 5.0

## Data Collection

Scanning engine: Professional scanner, one/two-dimensional barcode

Supported 1D barcode types  
UPC/EAN, Bookland EAN, UCC Coupon Code, ISSN EAN, Code 128, GS1-128, I SBT 128, Code 39, Trioptic Code 39, Code 32, Code 93, Code 11, Interleaved 2 of 5, Discrete 2 of 5, Codabar, MSI, Chinese 2 of 5, Korean 3 of 5, Matrix 2 of 5, Inverse 1D, GS1 DataBar, Composite Codes

Supported 2D barcode types  
PDF417, MicroPDF417, Data Matrix, Data Matrix Inverse, Maxicode, QR Code, MicroQR, QR inverse, Aztec, Aztec Inverse, Postal Codes: US Postnet, US Planet, UK Postal, Australian Postal, Japan Postal, Netherlands KIX Code, USPS 4CB/One/Intelligent Mail, UPS FICS Pstal

Cmera  
Front: 5MP FF  
Rear: 13MP AF, and 2MP FF secondary camera (optional)

## Internet of things function

NFC  
working band: 13.56MHz  
Support Protocol: MifareClassic (MF1) NDEF, NfcV (15693), Ultraligh (MF0), IsoDep (CPU MF3), IsoDep (CPU) Read Distance: 0-5cm

RFID  
Workingband: CHINA: 920-925MHz;  
USA: 902-928MHz; EU: 865-868MHz;  
Protocol: ISO18000-6C/EPC C1G2  
Read Distance: around 0.8m depends on the tags

Security PSAM  
Supporting ISO7816 standard, supporting 1PSAM cards

Sensors  
Light Sensor, distance sensor, gravity accelerometer, geomagnetic sensor, Hall Effect Sensor (Optional)

## Others

Certification  
CE/KCC/UN38.3/ROHS/IP67

Standard accessories  
5V/2A adapter/Data cable/battery/quick guide/UHF test tag

Optional accessories  
Charging cradle/charging cradle adapter/battery/temperedglass/hand strap/pistol grip/lanyard

Head office: 4th Floor, HuixiniBC Building A, Zhangba 1st Road, Hi-tech Zone, Xi'an, Shaanxi, China

Shenzhen branch: 2nd Floor, Building A, Runfeng industrial park, Gushu, Xixiang Street, Bao'an District, Shenzhen, China

E-mail: [contact@cilico.com](mailto:contact@cilico.com)

+86 29-8860 5865

+86 755-2912 0504



[www.cilico.com](http://www.cilico.com)