



C80R

UHF RFID Reader

Industry-leading RFID performance

Professional scanner with high speed and accuracy

- To make work efficient in real-time in reading 1D/2D even the twisted, stained or old barcode

10600mAh large capacity battery

- Plentiful power provides worry-free work
Replaceable battery, easy to use

Comfortable grab feel and not easily getting tired

- Ergonomic grip, anti-slip and anti-fatigue design for long time use, not easy to get tired








Powerful and easy long-distance batch reading

- Mainstream engine supports RFID tag batch reading up to 15-30 meters

Protection level

- IP67 sealing level
- 1.5m drop resistance, meets the IEC seal specifications

Features

 5.7" HD+ screen	 Octa-core 2.0GHz	 10600mAh Battery	 1D/2D
 Android 13	 15m-30m UHF reading distance	 IP67	 Super protection in bad weather

C80R Specifications

Basic Parameters

Size	169.9×76.8 X 26mm (L X W X H)
Weight	630+/-50g(with Battery)
Display	5.72inch IPS screen, resolution: (1440*720)
Touch screen	Capacitive touch, support wet hand and glove operation

Backlit LED Backlit

Battery Removable terminal battery: 6200mAh, 3.8V
Removable handgrip battery: 6000mAh, 3.8V
Working time: more than 8 hours, Standby time: 300 hours

Card slot 1 Nano SIM, 1 TF/Nano SIM
2 PSAM card slots, 1 Micro SD card slot (128GB Max)

Communication Interface Type-c, Support OTG

Network connections 4G/3G/2G, Wi-Fi, GPRS

Notification Tone, LED Indicator, Vibration

Keypad On-screen keypad+ 3 virtual buttons: Back, Home, Menu

Audio Microphone, speaker, receiver

Button Power key, Two scan keys, Volume +/- key, custom key

Power adapter Input: 100-240V, 50/60HZ 300Ma, Output: 5V, 2A

Performance Parameter

CPU Octa-core 2.0GHz

OS Android 13

Memory 4GB RAM/64GB ROM

User environment

Operating temperature -20°C to 55°C

Storage temperature -40°C to 70 °C

Humidity 5% to 95% (Non-condensation)

Drop Withstand multiple drops from 4.9 ft / 1.5m to concrete floor in operating temperature range

Roll Withstand 200 times 1.6 ft/0.5 m rolling impact, meets or exceeds IEC rolling specifications

Vibration Random (10 Hz-30KHz), 60 minutes per axis, 3 axes

ESD +/- 10kv air discharge, +/- 6kv contact discharge

Sealing Host IP67

Wireless Communication

WWAN **Asia + Europe band:**
GSM: Band 2/3/5/8
WCDMA: Band 1/2/5/8
TD-SCDMA: Band 34/39
CDMA: Band BC0
TDD-LTE: Band 34/38/39/40/41
FDD-LTE: Band 1/3/5/7/8/20

American band:
GSM: Band 2/3/5/8
WCDMA: Band 1/2/4/5 CDMA: Band BC0
TDD-LTE: Band 40/41
FDD-LTE: Band B1/2/4/5/7/28A/28B

WiFi 2.4GHz & 5GHz
Protocol: IEEE 802.11 a/b/g/n/ac/r/e/i Fast Roaming

GPS Beidou, Glonass, GPS, Galileo, QZSS

Bluetooth Bluetooth 5.0

Data capture

Bar code Engine Zebra/ Honeywell/Newland

1D Symbologies EAN-13, EAN-8, UPC-A, UPC-E, Code 128, Code 39, Codabar, UCC/EAN-128, RSS, ITF, ITF14, ITF6, ISSN, ISBN, Standard 25, Matrix 25, Industrial 25, Plessey, MSI Plessey, Code 11, Code 93, etc.

2D Symbologies PDF417, Micro PDF417, QR Code, Micro QR, DataMatrix, AZTEC, Maxicode, Composite, etc.

Camera Front-5MP (optional)
Rear-13MP, autofocus;
Rear camera flash; Support flashlight mode

ITO function

NFC working band: 13.56MHz
Support Protocol: MifareClassic (MF1) NDEF, NfcV (15693), Ultraligh (MF0), IsoDep (CPU MF3), IsoDep (CPU)
Read Distance: 0-4cm

RFID (UHF) Workingband: CHINA: 920-925MHz;
USA: 902-928MHz; EU: 865-868MHz;
Protocol: ISO18000-6C/EPC C1G2
Read Range: up to 15 meters (depending on tags)
Read Rate: up to 900 tags/sec (circular polarization)
Antenna: Circular polarization 4.5 dBi

Security PSAM Support 2PSAM cards. ISO7816 standard

Sensor Light sensor, distance sensor, Gravity sensor, geomagnetic sensor, Hall Sensor (optional)

Others

Certification CE/CCC/FCC/GMS/AER/RoHS/IP67/TAC/UN38.3

Standard accessories Adapter/data cable/battery/hand strap /NFC test card/ UHF test label

Optional accessories Charging cradle /charging cradle adapter/battery/tempered film

Head office: 4th Floor, HuixinIBC Building A, Zhangba 1st Road, Hi-tech Zone, Xi'an, Shaanxi, China

Shenzhen branch: 2nd Floor, Building A, Runfeng industrial park, Gushu, Xixiang Street, Bao'an District, Shenzhen, China

E-mail: contact@cilico.com

+86 29-8860 5865

+86 755-2912 0504



www.cilico.com